

2025 KLX230 BS6

Starting At Rs.TBA (Ex-Showroom)

Pricing will be announced in December 2024, Booking Starts at 5000/-

\*Product pictures shown are for illustration purpose only.

\*Actual product may vary from the picture shown here.

\*Specification and pricing are subject to change.



AVAILABLE COLOURS

Lime Green

Battle Grey

Engine & Transmission	
TYPE	Air-cooled, 4-stroke Single
DISPLACEMENT	233 cc
BORE AND STROKE	67.0 x 66.0 mm
COMPRESSION RATIO	9.4:1
VALVE SYSTEM	SOHC, 2 valves
FUEL SYSTEM	Fuel injection: ø32 mm x 1
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	Digital
STARTING	Electric Starter
LUBRICATION	Forced lubrication, wet sump
TRANSMISSION	6-speed, return
MAXIMUM POWER	13.3 kW {18.1 PS} / 8,000 rpm
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	18.3 N·m {1.87 kgf·m} / 6,400 rpm
ELECTRONIC RIDER AID	-
Dimensions & Chassis	
FRAME TYPE	Perimeter, high-tensile steel
RAKE / TRAIL	25.2º/ 101mm
TYRE - FRONT	2.75-21 45P
TYRE - REAR	4.10-18 59P
WHEELBASE	1,370 mm
GROUND CLEARANCE	265 mm
SEAT HEIGHT	880 mm
CURB MASS	139 kg
FUEL CAPACITY	7.6 Litres

**Dimensions & Chassis**

OVERALL DIMENSIONS (L X W X H)	2,090 x 845 x 1,150 mm
--------------------------------	------------------------

**Brakes & Suspension**

FRONT / WHEEL TRAVEL	37mm telescopic fork/7.8 in /240 mm
REAR / WHEEL TRAVEL	New Uni Trak with adjustable preload /250 mm
BRAKE - FRONT	Single ø265 mm petal disc
CALIPER - FRONT	Twin-piston
BRAKE - REAR	Single ø220 mm petal disc
CALIPER - REAR	Single-piston