

NEW 2018

Versys-X 300

TECHNICAL SPECIFICATION

Engine	:4-stroke Parallel Twin
Type	:Liquid-cooled
Displacement	:296 cm ³
Valve System	:DOHC, 8 valves
Power	:29.3 kW (40 PS) / 11,500 min ⁻¹
Torque	:25.7 N.m (2.6 kgf.m) / 10,000 min ⁻¹



Specifications

ENGINE

Type	: Liquid-cooled, 4-stroke Parallel Twin
Displacement	: 296 cm ³
Bore and Stroke	: 62.0 x 49.0 mm
Compression ratio	: 10.6:1
Valve system	: DOHC, 8 valves
Fuel system	: Fuel injection: ø 32 mm x 2 with dual throttle valves

Ignition	: Digital
Starting	: Electric
Lubrication	: Forced lubrication, wet sump
Transmission	: 6 speed, return
Maximum power	: 29.3 kW {40 PS} / 11,500 rpm
Maximum torque	: 25.7 N.m {2.6 kgf.m} / 10,000 rpm

VEHICLE

Frame Type	: Backbone, high-tensile steel
Rake / Trail	: 24.3° / 108 mm
Tyre	: Front: 100/90-19M/C 57S : Rear: 130/80-17M/C 65S
Wheelbase	: 1,450 mm
Ground clearance	: 180 mm
Seat height	: 815 mm
Curb mass	: 184 kg
Fuel capacity	: 17 Litres
Overall Dimensions	: 2,170 mm x 940 mm x 1,390 mm
LxWxH	

SUSPENSION

Front / Wheel Travel	: ø41 mm telescopic fork (130 mm)
Rear / Wheel Travel	: Bottom-Link Uni-Trak, gas-charged shock and adjustable preload (148 mm)

BRAKE

Brake Front	: Single ø290 mm petal disc
Caliper Front	: Single balanced actuation dual-piston
Brake Rear	: Single ø220 mm petal disc
Caliper Rear	: Dual-piston

