



30 KWPEAK POWER

155 KM/H

MAX SPEED

PEAK MOTOR TORQUE

100 NM

323 KM RANGE (IDC)



DESIGN

AERO SURFACES



Afterburner Yellow

LASER



Turbo Red

SHADOW



Cosmic Black

AIRSTRIKE



Stellar White

F SERIES -JET INSPIRED

DESIGN SERIES

DYNAMIC, STREET-ORIENTED

STANCE

PARALLAX & RADAR

CONSOLE THEMES





SUPERSTREET

SUPERSTREET RECON

PERFORMANCE

PEAK POWER 27 kW (36.2 hp) 30 kW (40.2 hp)

PEAK TORQUE 90 Nm 100 Nm

MAX SPEED 155 km/h 155 km/h

ACCELERATION (0-60 KMPH) 2.9 sec 2.8 sec

ACCELERATION (0-100 KMPH) 7.8 sec 7.7 sec

DYNAMIC REGENERATIVE BRAKING Included Included

LEVELS OF REGENERATIVE BRAKING 3 levels included 10 levels

10 levels optional

RIDE MODES Glide, Combat, Ballistic Glide, Combat, Ballistic

RANGE ESTIMATES

RANGE (IDC EST.) 211 km 323 km

RANGE GLIDE (AVG. 40 WH/KM) 183 km **266 km**

RANGE COMBAT (AVG. 52 WH/KM) 144 km **209 km**

RANGE BALLISTIC (AVG. 60 WH/KM) 128 km 186 km

SMART TECH

VIOLETTE A.I. Optional Optional

DELTA WATCH Optional Optional

LOCKDOWN Optional Optional

ANTI-COLLISION WARNING SYSTEM Optional Optional

CRASH ALERT Optional Optional

DAILY RIDE ANALYTICS Optional Optional

CONTROL CENTER Multi-function 5" TFT display with Multi-function 5" TFT display with

tactile input switch console (L+R) tactile input switch console (L+R)

OPERATING SYSTEM UV Automotive Linux OS UV Automotive Linux OS





SUPERSTREET

SUPERSTREET RECON

SAFETY Auto dimming LED Headlight with

Ultra-V position lamp

Dual LED tail light assembly with

central brake light

Front and Rear LED Hazard Lights

Sidestand Sensor

TRACTION CONTROL Optional

HILL HOLD Included

ABS Mono & Dual channel

D.S.C - DYNAMIC STABILITY CONTROL Included

CHARGE LIMIT Included

UTILITY

PARK ASSIST Included

FIND MY F77 Included

DEEP SLEEP Included

TPMS Optional

Auto dimming LED Headlight with Ultra-V position lamp

Dual LED tail light assembly with central brake light

Front and Rear LED Hazard Lights

Sidestand Sensor

4 levels

Included

Mono & Dual channel

Included

Included

Included

Included

Included

Optional

BATTERY SYSTEM

BATTERY PACK SRB7

ENERGY CAPACITY 7.1 kWh

BMS & SAFETY PROTOCOLS

Battery Management System with

Patented 5-level Safety System -Mechanical, Thermal, Electrical, Electronic & Software Protection

ENCLOSURE All-Aluminum IP67-rated Enclosure

SRB10

10.3 kWh

Battery Management System with Patented 5-level Safety System -Mechanical, Thermal, Electrical, Electronic & Software Protection

All-Aluminum IP67-rated Enclosure





Optional

Optional

SUPERSTREET

SUPERSTREET RECON

BATTERY & DRIVETRAIN WARRANTY

UV CARE 3 years or 60,000 km included

5 years or 1,00,000 km optional 5 years or 1,00,000 km included **UV CARE PLUS**

UV CARE MAX N/A 8 years or 8,00,000 km optional

VEHICLE WARRANTY

3 years or 30,000km* 3 years or 30,000km* STANDARD WARRANTY (VEHICLE)

CHARGING

CHARGING PORT IEC 62196-6 IEC 62196-6

UV SUPERNOVA PLUS Compatible Compatible

(12KW DC FAST CHARGING NETWORK) 20% - 80% in 45 min 20% - 80% in 60 min

UVLYNC INTERFACE Optional

(COMPATIBLE WITH TYPE 2 AC CAR CHARGING

NETWORK)

STANDARD **CHARGER**

Included Included

CHARGE RATE Up to 35 km of range per hour of Up to 35 km of range per hour of charge

charge

20% - 80% in 3 hrs 20% - 80% in 5 hrs

BOOST CHARGER Optional

CHARGE RATE Up to 75 km of range per hour of Up to 75 km of range per hour of

> charge charge

20% - 80% in 1.5 hrs 20% - 80% in 2.5 hrs

DRIVETRAIN

Permanent Magnet AC Motor Permanent Magnet AC Motor **MOTOR**

THROTTLE CONTROL Ride-by-wire Ride-by-wire





SUPERSTREET

SUPERSTREET RECON

MECHANICAL

FRAME Steel Trellis with Aluminium Bulk Head

FRONT SUSPENSION Upside-down Telescopic fork with a

diameter of 41 mm. Preload adjustable

REAR SUSPENSION Monoshock - preload adjustable

BRAKE SYSTEM Hydraulic disc brakes with dual-

channel BOSCH ABS

BRAKE CALIPERS Front: Fixed 4-Radial Piston Type

Rear: Single Piston Floating Caliper Type

BRAKE ROTOR Front: 320mm disc Rear: 230mm disc

TYRES Front: 110/70 R17 Rear: 150/60 R17

Steel Trellis with Aluminium Bulk Head

Upside-down Telescopic fork with a diameter of 41 mm. Preload adjustable

Monoshock - preload adjustable

Hydraulic disc brakes with dual-

channel BOSCH ABS

Front: Fixed 4-Radial Piston Type

Rear: Single Piston Floating Caliper Type

Front: 320mm disc Rear: 230mm disc

Front: 110/70 R17 Rear: 150/60 R17

CONNECTIVITY

NETWORK LTE connectivity with integrated eSIM LTE connectivity

WLAN Supports 802.11a/b/g/n/ac Wi-Fi

standards

BLUETOOTH Supports Bluetooth 5, Bluetooth low

energy

POSITIONING GPS/GLONASS

LTE connectivity with integrated eSIM

Supports 802.11a/b/g/n/ac Wi-Fi

standards

Supports Bluetooth 5, Bluetooth low

energy

GPS/GLONASS

DIMENSIONS

WHEEL BASE 1340 mm **1340 mm**

SEAT HEIGHT 800 mm 800 mm

KERB WEIGHT 197 kg **207 kg**

GROUND CLEARANCE 160 mm 160 mm