

























RS 457



RACING STRIPES



PRISMATIC DARK



OPALESCENT LIGHT

TUONO 457



PIRANHA RED



PUMA GREY

SR 175 hp.e



MATTE PRISMATIC DARK



GLOSSY TECH WHITE

SR 125 hp.e



GLOSSY MAZDA GREY + MATTE BLACK



GLOSSY RED + MATTE BLACK



MATTE BLACK

COLOUR RANGE 2025



	RS 457	Tuono 457		
ENGINE				
Туре	Parallel twin, 4 valves per cylinder liquid-cooled with Ride-By-Wire	Parallel twin, 4 valves per cylinder liquid-cooled with Ride-By-Wire		
Displacement	457 cc	457 cc		
Bare and Stroke	69 x 61.1 mm	69 x 61.1 mm		
Max. Power	47.6 HP (35 kW) @ 9,400 rpm	47.6 HP (35 kW) @ 9,400 rpm		
Max. Torque	43.5 Nm @ 6,700 rpm	43.5 Nm @ 6,700 rpm		
Clutch	Multi-plate wet clutch with slipper system	Multi-plate wet clutch with slipper system		
Gearbox	6 speed	6 speed		
CHASSIS				
Frame	Twin spar aluminum frame	Twin spar aluminum frame		
Front Suspension	Ø 41mm USD fork, adjustable preload, 120mm wheel travel	Ø 41mm USD fork, adjustable preload, 120mm wheel travel		
Rear Suspension	Monoshock, adjustable preload 130 mm wheel travel	Monoshock, adjustable preload 130 mm wheel travel		
Front Brake	Ø 320 mm floating disc, ByBre 4-piston radial calliper	Ø 320 mm floating disc, ByBre 4-piston radial calliper		
Rear Brake	Ø 220 mm disc, ByBre calliper	Ø 220 mm disc, ByBre calliper		
Front Wheel	Cast wheel 17" x 3"	Cast wheel 17" x 3"		
Rear Wheel	Cast wheel 17" x 4.5"	Cast wheel 17" x 4.5"		
DIMENSIONS & WEIGHTS				
Seat Height	800 mm	800 mm		
Fuel Tank Capacity	13 lt	12.7 lt		
Wet Weight*	175 Kg	175 Kg		

	RS 457	Tuono 457
STD. FEATURES		
Standard Features	Full LED Headlight and Indicators, 5" TFT Dashboard, Backlit Switchcubes, Engine maps (AEM), Dual-Channel ABS with Anti Roll Over System (2 maps), Traction Control (ATC), 3 Riding Modes, Metal Braided Brake Hoses.	Full LED Headlight and Indicators, 5" TFT Dashboard, Backlit Switchcubes, Engine maps (AEM), Dual-Channel ABS with Anti Roll Over System (2 maps), Traction Control (ATC), 3 Riding Modes, Metal Braided Brake Hoses.

WARRANTY

3 YEARS Manufacturer's warranty (36,000 kms*)

1 YEAR 3 free services (12,000 kms*)

2 YEARS Road-Side-Assistance with no extra cost.

- Coverage of repair costs for faults due to manufacturing of assembly defects of parts.
- Replacement of any damaged parts with OE spare parts, labour included.
- Roadside assistance including towing service.
- Specialized service assistance by Piaggio's authorized dealers.

The company reserves the right to make technical and aesthetic changes at any time. Full information on models and accessories is available at www.aprilia.com. Ride carefully, always wearing a helmet and suitable gear. Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with current legislation. Visit an Official Aprilia Dealership or Authorised Retailer for a secure purchase and quaranteed service support.

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV
= ISO 14001 =

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = ISO 9001= COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV = OHSAS 18001=

Aprilia is a registered trademark of Piaggio & C. S.p.A.

*According to regulation (EU) No 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.

	SR 175 hp.e	SR 125 hp.e		
ENGINE				
Туре	Single cylinder, 4 stroke, SOHC 3 valve	Single cylinder, 4 stroke, SOHC 3 valve		
Cylinder Bore	60.6 mm	52 mm		
Stroke	60.6 mm	58.6 mm		
Piston Displacement	174.7 cm³	124.45 cm³		
Compression Ratio	9.5:1	10:1		
Fuel Pump	KEIHIN	KEIHIN		
Power Supply	Electronic injection with throttle body, Single injector	Electronic injection with throttle body, Single injector		
Air Filter	Paper Type	Paper Type		
Lubrication System	Forced feed circulation, wet sump	Forced feed circulation, wet sump		
Maximum Power	9.76 kW @7200 RPM	7.8 kW @7400 RPM		
Maximum Torque in Nm	14.14 Nm @ 6000 RPM at crankshaft	10.4 Nm @ 6200 RPM at crankshaft		
Maximum Speed	95 km/hr	90 km/hr		
Engine Idling RPM	1800±100	1800±100		
Starting System	Electric Starter	Electric Starter		
TRANSMISSION				
Clutch	Self Ventilating Dry Centrifugal Clutch	Self Ventilating Dry Centrifugal Clutch		
Transmission	Auto Expendable - CVT with forced circulation air cooling	Auto Expendable - CVT with forced circulation air cooling		
Primary Reduction	0.802:1 - 2.801:1	0.802:1 - 2.801:1		
Final Reduction	9:48 : 1	11.73 : 1		

WARRANTY

5 YEARS Manufacturer's warranty (60,000 kms*)

1 YEAR 4 free services (*kms range defined in Owner's manual)

2 YEARS Road-Side Assistance with no extra cost.

- Coverage of repair costs for faults due to manufacturing or assembly defects of parts.
- Replacement of any damaged parts with OE spare parts, labour included.
- Roadside assistance including towing service.
- Specialized service assistance by Piaggio's authorized dealers.

The company reserves the right to make technical and aesthetic changes at any time. Full information on models and accessories is available at www.aprilia.com. Ride carefully, always wearing a helmet and suitable gear. Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with current legislation. Visit an Official Aprilia Dealership or Authorised Retailer for a secure purchase and quaranteed service support.

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV
= ISO 14001=

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001=

COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV = OHSAS 18001=

Aprilia is a registered trademark of Piaggio & C. S.p.A.

*According to regulation (EU) No 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume.

aprilia®

apriliaindia.com